

Project:	
Location:	
Model#: ELMWEM	Type:
Client:	Qty:
Prepared by:	Date:

SERIES SPECIFICATIONS



The ELMWEM is a micro adjustable LED emergency light that utilizes fully adjustable heads, a long life Ni-Cad battery and is constructed with a easy to install snap-together design



PERFORMANCE SPECIFICATIONS

Initial Lumen Output: 220 lm	Beam Angle: 23.80	Luminaire Type: Emergency light
Environmental Rating(s): Damp location	Ambient Operating Temp: 10°C to 40°C / 50°F to +104°F	Certification Standards: UL924, C22.2 No. 141-15
Limited Product Warranty: 2 years for battery 3 years for fixture		

LED SPECIFICATIONS

Source Type: LED	CRI: > 80	L70: >54,000 Hrs
Colour Temperature: 5700K		

ELECTRICAL SPECIFICATIONS

Input Voltage: 120/277V	Input Frequency: 50/60 Hz	Current Draw at 120Vac: 58mA
Current Draw at 277Vac: 72mA	Inrush Current: ~30A	Max On-Delay: 1S
Power Factor at 120Vac: > 0.4	Power Factor at 277Vac: > 0.4	Power Factor at 347Vac: > 0.4
Max Operating Case Temperature: 40?	Surge Suppression: YES	Short Circuit Protection: YES

EMERGENCY INFORMATION

Input Voltage: 120/277V	Max Power Input: 0.5W	Standby Power: 0.5W
Emergency Runtime: >90minutes	Battery Type: Ni-cad	Battery Recharge Time: 24hours
Emergency Certifications: UL924		



Project:	
Location:	
Model#: ELMWEM	Type:
Client:	Qty:
Prepared by:	Date:

PHYSICAL SPECIFICATIONS

Finish Colour: White
Lens Material: Polycarbonate

Mounting: Wall or Ceiling
Weight: 0.47 kg

Housing Material: ABS

SHIPPING INFORMATION

OrderingCode(s): 0627-8568 ELMWEM
LED MICRO EM LIGHT 120/277
Carton Quantity: 12

Box Quantity: 1
Carton Dimensions (I-W-H): 354 x 204 x
234 mm / 0.1 x 0 x 354 inches

Box Dimensions (L-W-H): 203 x 127 x 76
mm / 8 x 5 x 3 inches
Carton Weight: 005.5 Kg