

Project:	
Location:	
Model#: ELMWEM	Type:
Client:	Qty:
Prepared by:	Date:

## SERIES SPECIFICATIONS



The ELMWEM is a micro adjustable LED emergency light that utilizes fully adjustable heads, a long life Ni-Cad battery and is constructed with a easy to install snap-together design



## PERFORMANCE SPECIFICATIONS

**Initial Lumen Output:** 220

**Environmental Rating(s):** Damp location

**Limited Product Warranty:** 2 years for battery, 3 years for fixture

**Beam Angle:** 23.8

**Ambient Operating Temp:** 10°C to 40°C / 50°F to +104°F

**Luminaire Type:** Emergency light

**Certification Standards:** UL924, C22.2 No. 141-15

## LED SPECIFICATIONS

**Source Type:** LED

**Colour Temperature:** 5700

**CRI:** > 80

**L70:** >54,000 Hrs

## ELECTRICAL SPECIFICATIONS

**Input Voltage:** 120/277V

**Current Draw at 277Vac:** 72mA

**Power Factor at 120Vac:** > 0.4

**Max Operating Case Temperature:** 40°

**Input Frequency:** 50/60 Hz

**Inrush Current:** ~30A

**Power Factor at 277Vac:** > 0.4

**Surge Suppression:** YES

**Current Draw at 120Vac:** 58mA

**Max On-Delay: Power Factor at 347Vac:** > 0.4

**Short Circuit Protection:** YES

## EMERGENCY INFORMATION

**Input Voltage:** 120/277V

**Emergency Runtime:** >90minutes

**Emergency Certifications:** UL924

**Max Power Input:** 0.5W

**Battery Type:** Ni-cad

**Standby Power:** 0.5W

**Battery Recharge Time:** 24hours

Project:	
Location:	
Model#: ELMWEM	Type:
Client:	Qty:
Prepared by:	Date:

#### PHYSICAL SPECIFICATIONS

**Finish Colour:** White  
**Lens Material:** Polycarbonate

**Mounting:** Wall, ceiling  
**Weight:** 0.47 kg

**Housing Material:** ABS

#### SHIPPING INFORMATION

**OrderingCode(s):** 0627-8568 ELMWEM  
LED MICRO EM LIGHT 120/277  
**Carton Quantity:** 12

**Box Quantity:** 1  
**Carton Dimensions (L-W-H):** 354 x 204 x  
234 mm / 0.1 x 0 x 354 inches

**Box Dimensions (L-W-H):** 203 x 127 x 76  
mm / 8 x 5 x 3 inches  
**Carton Weight:** 5.5

#### LINE DRAWING

##### Line Drawings

