

	Project:	
'	Location:	
	Model#: ELWWRC	Туре:
	Client:	Qty:
	Prepared by:	Date:

SERIES SPECIFICATIONS



The ELWWRC is a wet location emergency light designed to illuminate the path of egress in environments where this fixture may be in contact with water. This includes two(2) adjustable heads rated at 300 lumens per head.



PERFORMANCE SPECIFICATIONS		
Initial Lumen Output: 2 X 300 Im Environmental Rating(s): Wet location Certification Standards: UL924, C22.2 No. 141-15	Beam Angle: 28.5 Fire Rating: 5VA Limited Product Warranty: 2 years for battery, 3 years for fixture	Luminaire Type: Emergency light Ambient Operating Temp: 0°C to 50°C / 32°F to +122°F
LED SPECIFICATIONS		
Source Type: LED Colour Temperature: 5700	CRI: > 80	L70: >54,000 Hrs
ELECTRICAL SPECIFICATIONS		
Input Voltage: 120-347V Current Draw at 347Vac: 45mA Power Factor at 120Vac: > 0.4 Max Operating Case Temperature: 50? Short Circuit Protection: YES	Input Frequency: 50/60 Hz Inrush Current: ~30A Power Factor at 277Vac: > 0.4 Surge Suppression: YES	Current Draw at 120Vac: 25mA Max On-Delay: Power Factor at 347Vac: > 0.4 Over Temperature Protection: YES
EMERGENCY INFORMATION		
Input Voltage: 120-347V Emergency Runtime: >90minutes Emergency Certifications: UL924	Max Power Input: 3.5W Battery Type: Ni-cad	Standby Power: 0.95W Battery Recharge Time: 24hours



Project:	
Location:	
Model#: ELWWRC	Туре:
Client:	Qty:
Prepared by:	Date:
	Location: Model#: ELWWRC Client:

PHYSICAL SPECIFICATIONS

Finish Colour: White Lens Material: Polycabonate Mounting: Wall Weight: 1.24 kg Housing Material: Polycabonate

SHIPPING INFORMATION

OrderingCode(s): 0627-8571 ELWWRC LED EM LIGHT RC 120-347 Carton Quantity: 6 **Box Quantity:** 1 **Carton Dimensions (I-W-H):** 460 x 330 x 280 mm / 0.3 x 0 x 460 inches **Box Dimensions (L-W-H):** 330 x 279 x 76 mm / 13 x 11 x 3 inches **Carton Weight:** 7.4



	Project:	
•	Location:	
	Model#: ELWWRC	Туре:
	Client:	Qty:
	Prepared by:	Date:

LINE DRAWING

Line Drawings

