


Project:	
Location:	
Model#: ELWWRC	Туре:
Client:	Qty:
Prepared by:	Date:

#### **SERIES SPECIFICATIONS**



The ELWWRC is a wet location emergency light designed to illuminate the path of egress in environments where this fixture may be in contact with water. This includes two(2) adjustable heads rated at 300 lumens per head.










### PERFORMANCE SPECIFICATIONS

## **Luminance Distribution Chart**



Initial Lumen Output: 2 X 300 Im Environmental Rating(s): Wet location

(0°C to 50°C)

Limited Product Warranty: 2 years for

battery 3 years for fixture

Beam Angle: 28.50

Ambient Operating Temp: 0°C to 50°C /

32°F to +122°F

Luminaire Type: Emergency light Certification Standards: UL924, C22.2

No. 141-15



Project:		
Location:		
Model#: ELWWRC	Туре:	
Client:	Qty:	
Prepared by:	Date:	

#### LED SPECIFICATIONS

**Source Type:** LED **CRI:** > 80 **L70:** >54,000 Hrs

Colour Temperature: 5700K

## **ELECTRICAL SPECIFICATIONS**

Input Voltage: 120-347V Input Frequency: 50/60 Hz Current Draw at 120Vac: 25mA

Power Factor at 120Vac: > 0.4 Power Factor at 277Vac: > 0.4 > 0.4

Max Operating Case Temperature: 50? Surge Suppression: YES Over Temperature Protection: YES

Short Circuit Protection: YES

EMERGENCY INFORMATION

Input Voltage: 120-347V Max Power Input: 3.5W Standby Power: 0.95W

Emergency Runtime: >90minutes Battery Type: Ni-cad Battery Recharge Time: 24hours

Emergency Certifications: UL924

PHYSICAL SPECIFICATIONS

Finish Colour: White Mounting: Wall or Ceiling Housing Material: Polycarbonate

Lens Material: Polycarbonate Weight: 1.24 kg

SHIPPING INFORMATION

OrderingCode(s): 0627-8571 ELWWRC Box Quantity: 1 Box Dimensions (L-W-H): 330 x 279 x 76

WET LOCATION LED EM LIGHT 120-347 Carton Dimensions (I-W-H): 460 x 330 x mm / 13 x 11 x 3 inches

 Carton Quantity: 6
 280 mm / 0.3 x 0 x 460 inches
 Carton Weight: 007.4 Kg



Project:	
Location:	
Model#: ELWWRC	Туре:
Client:	Qty:
Prepared by:	Date:

# LINE DRAWING

# **Line Drawings**

