

Project:		
Location:		
Model#:	RM3GWEM	Type:
Client:		Qty:
Prepared by:		Date:

SERIES SPECIFICATIONS



The RM3GWEM is a thermoplastic running man LED exit which offers a modern look with long lamp life, energy efficiency and uniform illumination; all components feature a snap-fit construction for speed and ease of installation. The unit also comes with a LED indicator for charge rate, "ON" and a push to test switch. Mounting canopy also included.



PERFORMANCE SPECIFICATIONS

Luminaire Type: Exit sign

Certification Standards: UL924, C22.2
No. 141-15

Environmental Rating(s): Damp location

Limited Product Warranty: 2 years for
battery 3 years for fixture

Ambient Operating Temp: 10°C to 40°C /

50°F to +104°F

LED SPECIFICATIONS

Source Type: LED

CRI: > 80

L70: >54,000 Hrs

Colour Temperature: 6000K

ELECTRICAL SPECIFICATIONS

Input Voltage: 120/347V

Input Frequency: 50/60 Hz

Current Draw at 120Vac: 52mA

Current Draw at 347Vac: 20mA

Inrush Current: 1A

Max On-Delay: 1S

Power Factor at 120Vac: > 0.4

Power Factor at 277Vac: > 0.4

Power Factor at 347Vac: > 0.4

Max Operating Case Temperature: 40

Surge Suppression: YES

Short Circuit Protection: YES

EMERGENCY INFORMATION

Input Voltage: 120/347V

Emergency Runtime: >90minutes

Emergency Certifications: UL924, Charge rate/power "ON" and push to test switch

Max Power Input: 6W

Battery Type: Ni-cad

Standby Power: 3W

Battery Recharge Time: 24hours

PHYSICAL SPECIFICATIONS

Finish Colour: White

Lens Material: Polycarbonate

Mounting: Back, Top or side mount.

Canopy included

Housing Material: ABS

Weight: 1.64 kg

SHIPPING INFORMATION

Ordering Code(s): 0627-8577 RM3GWEM

LED RM PLASTIC EM 120/347V

Carton Quantity: 6

Box Quantity: 1

Carton Dimensions (I-W-H): 410 x 370 x

255 mm / 0.3 x 0 x 410 inches

Box Dimensions (L-W-H): 356 x 254 x 76

mm / 14 x 10 x 3 inches

Carton Weight: 009.8 Kg

LINE DRAWING

Line Drawings

