

Project:	
Location:	
Model#: RM3GWEM	Туре:
Client:	Qty:
Prepared by:	Date:

SERIES SPECIFICATIONS



The RM3GWEM Is a thermoplastic running man LED exit which offers a modern look with long lamp life, energy efficiency and uniform illumination; all components feature a snap-fit construction for speed and ease of installation. The unit also comes with a LED indicator for charge rate, "ON" and a push to test switch. Mounting canopy also included.









PERFORMANCE SPECIFICATIONS

Luminaire Type: Exit sign

Certification Standards: UL924, C22.2

No. 141-15

Environmental Rating(s): Damp location

Limited Product Warranty: 2 years for

battery 3 years for fixture

Ambient Operating Temp: 10°C to 40°C /

50°F to +104°F

LED SPECIFICATIONS

Source Type: LED

Colour Temperature: 6000

CRI: > 80

L70: >54,000 Hrs

ELECTRICAL SPECIFICATIONS

Input Voltage: 120/347V

Current Draw at 347Vac: 20mA

Power Factor at 120Vac: > 0.4

Max Operating Case Temperature: 40?

Input Frequency: 50/60 Hz

Inrush Current: Power Factor at 277Vac:

> 0.4

Surge Suppression: YES

Current Draw at 120Vac: 52mA

Max On-Delay: Power Factor at 347Vac:

> 0.4

Short Circuit Protection: YES

EMERGENCY INFORMATION

Input Voltage: 120/347V

Emergency Runtime: >90minutes
Emergency Certifications: UL924,
Charge rate/power "ON" and push to test

switch

Max Power Input: 6W
Battery Type: Ni-cad

Standby Power: 3W

Battery Recharge Time: 24hours



Project:	
Location:	
Model#: RM3GWEM	Туре:
Client:	Qty:
Prepared by:	Date:

PHYSICAL SPECIFICATIONS

Finish Colour: White Mounting: Back, Top or side mount.

Lens Material: Polycabonate Canopy included

Weight: 1.64 kg

Housing Material: ABS

SHIPPING INFORMATION

OrderingCode(s): 0627-8577 RM3GWEM

LED RM PLASTIC EM 120/347V

Carton Quantity: 6

Box Quantity: 1

Carton Dimensions (I-W-H): 410 x 370 x

255 mm / 0.3 x 0 x 410 inches

Box Dimensions (L-W-H): 356 x 254 x 76

mm / 14 x 10 x 3 inches

Carton Weight: 9.8

LINE DRAWING

Line Drawings

