


Project:	
Location:	
Model#: RHR1-MULTI-WP	Туре:
Client:	Qty:
Prepared by:	Date:

### **SERIES SPECIFICATIONS**



The RHR Series is a thermoplastic wet location remote head designed for indoor and outdoor applications. To be used as part of an Emergency lighting system providing illumination for the path of egress.








### PERFORMANCE SPECIFICATIONS

## **Luminance Distribution Chart**



Initial Lumen Output: 100 lm Luminaire Type: Remote head Certification Standards: UL924, C22.2

No. 141-15

Efficacy: 100 lm/W

Environmental Rating(s): Wet location Limited Product Warranty: 3 years for

fixture

Beam Angle: 27.40

Ambient Operating Temp: -25°C to 50°C

 $/ -13^{\circ}F$  to  $+122^{\circ}F$ 



Project:	
Location:	
Model#: RHR1-MULTI-WP	Туре:
Client:	Qty:
Prepared by:	Date:

### **LED SPECIFICATIONS**

**Source Type:** LED **CRI:** > 80 **L70:** >54,000 Hrs

Colour Temperature: 5700K

**ELECTRICAL SPECIFICATIONS** 

Input Voltage: 3-12VDC Fixture Draw: 1W Max On-Delay: Short Circuit Protection:

Max Operating Case Temperature: 50? Over Temperature Protection: YES YES

**EMERGENCY INFORMATION** 

Input Voltage: 3-12VDC Max Power Input: 1W Emergency Certifications: Meets UL 924,

cULus, NFPA 101 Life Safety Code, NEC,

OSHA, Local and State Codes

PHYSICAL SPECIFICATIONS

Finish Colour: White Mounting: Wall, ceiling Housing Material: Aluminium /

260 mm / 0.1 x 0 x 380 inches

Lens Material: Polycabonate Reflector Material: ABS Polycarbonate

Weight: 0.24 kg

SHIPPING INFORMATION

OrderingCode(s): 0627-8562 RHR1
MULTI-WP ROUND REMOTE HEAD - 1

Carton Dimensions (I-W-H): 380 x 350 x

HEAD

Carton Quantity: 12

DX Quantity: 1 Box Dimensions (L-W-H): 127 x 127 x

178 mm / 5 x 5 x 7 inches **Carton Weight:** 003.9 Kg



Project:	
Location:	
Model#: RHR1-MULTI-WP	Туре:
Client:	Qty:
Prepared by:	Date:

# LINE DRAWING

# **Line Drawings**



