


Project:	
Location:	
Model#: RHR2-MULTI-WP	Туре:
Client:	Qty:
Prepared by:	Date:

SERIES SPECIFICATIONS



The RHR Series is a thermoplastic wet location remote head designed for indoor and outdoor applications. To be used as part of an Emergency lighting system providing illumination for the path of egress.








PERFORMANCE SPECIFICATIONS

Luminance Distribution Chart



Initial Lumen Output: 200 lm Luminaire Type: Remote head Certification Standards: UL924, C22.2

No. 141-15

Efficacy: 100 lm/W

Environmental Rating(s): Wet location Limited Product Warranty: 3 years for

fixture

Beam Angle: 27.40

Ambient Operating Temp: -25°C to 50°C

/ -13°F to +122°F



Project:	
Location:	
Model#: RHR2-MULTI-WP	Туре:
Client:	Qty:
Prepared by:	Date:

LED SPECIFICATIONS

Source Type: LED **CRI:** > 80 **L70:** >54,000 Hrs

Colour Temperature: 5700K

ELECTRICAL SPECIFICATIONS

Input Voltage: 3-12VDC Fixture Draw: 2W Max On-Delay: Short Circuit Protection:

Max Operating Case Temperature: 50? **Over Temperature Protection: YES**

EMERGENCY INFORMATION

Input Voltage: 3-12VDC Emergency Certifications: Meets UL 924, Max Power Input: 2W

cULus, NFPA 101 Life Safety Code, NEC,

OSHA, Local and State Codes

PHYSICAL SPECIFICATIONS

Finish Colour: White Mounting: Wall, ceiling Housing Material: Aluminium /

Lens Material: Polycabonate Reflector Material: ABS Polycarbonate

Weight: 0.38 kg

SHIPPING INFORMATION

OrderingCode(s): 0627-8565 RHR2-MULTI-WP ROUND REMOTE HEAD - 2

HEADS

Carton Quantity: 12

Box Quantity: 1

Carton Dimensions (I-W-H): 580 x 350 x

410 mm / 0.3 x 0 x 580 inches

Box Dimensions (L-W-H): 305 x 178 x

127 mm / 12 x 7 x 5 inches Carton Weight: 007.0 Kg



Project:	
Location:	
Model#: RHR2-MULTI-WP	Туре:
Client:	Qty:
Prepared by:	Date:

LINE DRAWING

Line Drawings



