


# TAMLITE

## L I G H T I N G



Tamlite Lighting Canada  
 10 Perdue Crt. Caledon, ON  
 HBX20050K-UNV-WH  
 4FT 205W LED HIGHBAY LUMINAIRE  
 LED 5000K  
 VOLTAGE 118.5 V  
 CURRENT 1.750 A  
 POWERFACTOR 0.991

Horizontal Footcandles  
 Scale: 1 Inch = 20 Ft.  
 Light Loss Factor = 1.00  
 Lumens Per Lamp = N.A. (absolute photometry)  
 Luminaire Lumens = 28657  
 Mounting Height = 20.00 Ft  
 Maximum Calculated Value = 23.92 Fc  
 Arrangement: Single

PHOTOMETRIC FILENAME : TCA\_IES\_HBX20050K-UNV.IES

**DESCRIPTIVE INFORMATION (From Photometric File)**

Tamlite Lighting Canada  
10 Perdue Crt. Caledon, ON  
HBX20050K-UNV-WH  
4FT 205W LED HIGHBAY LUMINAIRE  
LED 5000K  
VOLTAGE 118.5 V  
CURRENT 1.750 A  
POWERFACTOR 0.991

**TEMPLATE SPECIFICATION**

Horizontal Footcandles  
Scale: 1 Inch = 20 Ft.  
Light Loss Factor = 1.00  
Lumens Per Lamp = N.A. (absolute photometry)  
Luminaire Lumens = 28657  
Mounting Height = 20.00 Ft  
Maximum Calculated Value = 23.92 Fc  
Arrangement: Single

**LUMINAIRE LAYOUT INFORMATION**

<u>#</u>	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Orient</u>	<u>Tilt</u>	<u>Roll</u>	<u>Spin</u>	<u>Tilt Correction</u>
1	0.00	0.00	20.00	0.00	0.00	0.00	0.00	1.00