

PROJECT:	
LOCATION:	
MODEL#: TLPE244035K-347V-WH	TYPE:
CONTRACTOR:	QTY:
PREPARED BY:	DATE: __/__/__

SERIES SPECIFICATIONS



To supply and install TamLite's TLPE Series of LED Panel fixture as specified. The Luminaire shall operate at 347VAC and use an Everlight approved driver. The frame shall be constructed of painted aluminium with a PMMA diffuser. LEDs shall be as specified Everlight 67-21S LED chips. The luminaire shall be cULus listed



PERFORMANCE SPECIFICATIONS

Initial Lumen Output: 4,161 lm

Luminaire Type: Direct

UL Classification: Dry Location Only

CCN Number: IFA07.E470484

Efficacy: 114.0 lm/W

Spacing Criteria: 1.30 (Along), 1.30 (Across)

Ambient Operating Temp: -20°C to +40°C

Limited Product Warranty: 5 Years


CBCP: 1,500.00 cd

Environmental Rating(s): IP20

DLC Number: PL0VNFNSYZXK

LED SPECIFICATIONS

SPD



Source Type: LED

CRI: >80

Colour Tolerance: 3 SDCM

Manufacturer: Everlight®

L90: 54,000 Hrs

Duv:

Part Number: 67-21S

Colour Temperature: 3406K



PROJECT:	
LOCATION:	
MODEL#: TLPE244035K-347V-WH	TYPE:
CONTRACTOR:	QTY:
PREPARED BY:	DATE: __/__/__

ELECTRICAL SPECIFICATIONS

Input Voltage: 347VAC

Short Circuit Protection: Auto Recovery.

The output shall return to normal when the fault condition is removed.

Input Frequency: 50-60Hz

Dimming: 1-10VDC - 10% Min Light Level

Driver Certifications: c-RU-us Class 2,
FCC Part 15 Class B, RoHS

Fixture Draw: 037.29 W

Dimming Current mA: 0.200 mA

PHYSICAL SPECIFICATIONS

Finish Colour: White

Housing Material: Aluminium

Weight: 9.10 kg

Finish Type: Powder Coated

Lens Material: PMMA

Entries: 4 .500" Knockouts

Wiring: Junction Box

Lens Type: Diffuser

SHIPPING INFORMATION

OrderingCode(s): TLPE244035K-347V-WH

Box Weight: 009.5 Kg

Box Quantity: 2

Box Dimensions (L-W-H): 715x715x115
mm

SERIES ARCHITECTURE

Optional Extras: TLP24SMK-WH TLP24SPK TLP24DFK-WH